

DECLARATION OF PERFORMANCE

No.01/TM/ BĂICOI



1. Name of the product: **Metallic roofing tile: WETTERBEST CLASIC; WETTERBEST GLADIATOR;
WETTERBEST PLUS; WETTERBEST CARDINAL; WETTERBEST COLOSSEUM**
2. Intended use: **Roof coverings.**
3. Manufacturer: **S.C. Wetterbest S.A**
Înfratirii nr. 142
105200, Baicoi, Prahova County, Romania
4. Authorised representative: **Not applicable**
5. AVCP level: **Reaction to fire: 3; other properties: 4**
6. Harmonized standard: **SR EN 14782:2006** Self-supporting metal sheet for roofing, external cladding and internal lining. Product specification and requirements
7. Declared performance: The technical characteristics of the above mentioned product are available in the appendix accompanying this **Declaration of Performance**.

The performance of the product mentioned above is in accordance with the stated performance set.

This Declaration of Performance was issued in accordance with the legislation in force by Government Decision no. 668/2017 on establishing the conditions for marketing construction products with Regulation (EU) no. 305/2011 and on the exclusive responsibility of the manufacturer mentioned above.

This Declaration of Performance is available at the time of delivery and on the website: <https://www.wetterbest.ro>

Signed as or on behalf of the manufacturer by:

Ciulacu Marian Ionut.
EHSQ Manager
S.C. Wetterbest S.A

[illegible signature]

Baicoi, 01.02.2020

Annex 1 to the Declaration of Performance 01/TM/ BĂICOI

Manufacturer: S.C. Wetterbest S.A

Înfrățirii nr. 142; 105200, Băicoi, Prahova County; Romania

1

Product Declared values		WETTERBEST CLASIC			WETTERBEST PLUS		WETTERBEST GLADIATOR		WETTERBEST CARDINAL		WETTERBEST COLLOSEUM	
		SR EN 14782: 2006										
Year in which the CE marking was applied:		2012			2014		2016		2019		2017	
Mechanical resistance		NPD										
Water permeability		Waterproof- SR EN 14782: 2006										
Dimensional variation		Steel 12 x 10 ⁻⁶ x K ⁻¹										
Dimensional tolerance		Material thickness SR EN 10143: 2008 Form variation SR EN 508-1: 2014										
Emission of hazardous substances		NPD										
Outdoor fire performance		Classes B ROOF(1,2,3), roof coverings, NPD for other use										
Reaction to fire		Glossy polyester 25 µm A1: Mat polyester 35 µm A2-s1, d0: Neomat 30- 60µm A1-s1, d0; Suprem 50- 50µm A2-s1, d0										
DURABILITY	Material	DX 51 D+Z 225; S 280 GD+ Z 275;										
	Thickness	0.4	0.45	0.5	0.5	0.45	0.5	0.45	0.5	0.5		
	Organic coating SP 1 [µm]	L/25 µm	L/25 µm M/35 µm	L/25 µm	L/25 µm	M/35 µm	L/25 µm	M/35 µm	L/25 µm	M/35 µm	L/25 µm	
				M/35 µm	M/35 µm		M/35 µm		M/35 µm		M/35 µm	
				N/60µm	N/60µm		N/60µm		N/60µm		N/60µm	
S/50 µm				S/50 µm	S/50 µm		S/50 µm		S/50 µm			
Organic coating SP 2 [µm]	Min 7 µm											